




Computer Hardware Design

- ✓ Heavy duty
- ✓ Microsoft Windows drivers available
- ✓ OPOS drivers available
- ✓ Splash proof cover



CHD TH308S

Thermal Printer

Specification

| | |
|-----------------------------|---|
| Dimensions (mm): | 145 (W) x 205 (L) x 143 (H) |
| Case: | plastic |
| Case colour: | dark grey |
| Power: | 24V DC 2A |
| Operating temp.: | 0°C - 50°C |
| Operating humidity: | 80% max |
| Sensors: | paper end, cover open |
| Indicators: | paper end, cover open |
| Interface: | RS232C and USB and Ethernet and cash drawer |
| Printer: | thermal direct |
| Printing method: | thermal line dot printing |
| Number of dots/line: | 576 |
| Resolution: | 8 dots/mm |
| Paper width: | 80 mm |
| Printing width: | 72 mm |
| Paper roll size: | 80mm, Ø 80 mm |
| Speed max: | 200 mm/sec. |
| Cutter: | full cut or partial cut |
| Printer head life: | 100 million |
| Abrasion resistance: | 100 km |
| Cutter life: | 1 000 000 cuts |



Asia headquarters: CHD ASIA PTE. LTD., 3791 Jalan Bukit Merah #10-14, e-Centre, Singapore, 159471

Phone: +65 6271 0053, Fax: +65 6271 2053

Europe headquarters: Dzelzavas 120i, Riga, LV-1021, Latvia, Phone: +37167802812, Fax: +37167802822

info@chd.sg, www.chd.sg