



Computer Hardware Design

- ✓ Heavy duty
- ✓ Vertical or horizontal placement on the table
- ✓ USB, Ethernet and RS232 interfaces
- ✓ WiFi and BT onboard
- ✓ Microsoft® Windows™, OPOS drivers available



CHD TH508

Thermal Printer

Specification

Printer:	thermal direct
Print mechanism:	SII CAP06-347-A1
Printing method:	thermal line dot printing
Number of dots/line:	576
Resolution:	230 dpi or 8 dots/mm
Paper width:	80 mm
Printing width:	72 mm
Paper roll size:	80mm, Ø 80 mm
Speed max:	250 mm/sec.
Cutter:	full cut or partial cut
Printer head life:	150 million or more
Abrasion resistance:	100 km or more
Cutter life:	1 500 000 cuts or more
Dimensions (mm):	130 (W) x 130 (L) x 130 (H)
Case:	plastic
Case colour:	dark grey
Power:	24V DC 2.5A
Operating temp.:	-10°C to +50°C
Operating humidity:	85% max
Sensors:	paper end, cover open
Indicators:	paper end, cover open
Printer position:	vertical or horizontal
Interface:	USB, Ethernet, WiFi/BT and RS232 (option)
Cash drawer:	RJ11
Wall mount:	yes



Rev.: 19.01.2021